

98
0

Clés polygonales contrecoudées


IEC 60900 DIN EN 60900



98 01 14

⚡ 1000V ○

- coudée
- outil de base chromé
- Acier au chrome-vanadium, forgé, trempé à l'huile



Réf.	EAN 4003773-		Ouverture de clé S mm	Long. l max. mm	Largeur de tête b max. mm	Épaisseur de tête a max. mm	Hauteur du coudage h max. mm	⚖ g
98 01 07	020134	⚡ 1000V ○	7,0	150,0	12,0	7,0	18,0	55
98 01 08	020141		8,0	155,0	14,0	7,0	19,0	68
98 01 09	020158		9,0	165,0	15,5	8,0	19,0	78
98 01 10	020196		10,0	160,0	17,0	9,0	20,0	75
98 01 11	020202		11,0	165,0	18,5	10,0	21,0	93
98 01 12	020226		12,0	185,0	18,5	10,0	23,0	118
98 01 13	020233		13,0	185,0	21,5	11,0	23,0	125
98 01 14	020240		14,0	195,0	23,0	12,0	24,0	147
98 01 15	020257		15,0	200,0	24,0	12,0	24,0	143
98 01 16	020264		16,0	200,0	26,0	12,0	26,0	172
98 01 17	020271		17,0	205,0	27,0	13,0	26,0	184
98 01 18	020288		18,0	210,0	29,0	13,0	28,0	210
98 01 19	020295		19,0	225,0	30,0	14,0	28,0	245
98 01 22	020301		22,0	225,0	35,0	15,0	30,0	268
98 01 24	020318		24,0	265,0	38,0	16,0	30,0	961