

Douilles à six pans

avec carré femelle 3/8" ou 1/2"

IEC 60900 DIN EN 60900

- pour vis à six pans métriques ou en pouces
- outil de base chromé
- Acier au chrome-vanadium



97 37 17

⚡ 1000V ○ 100%

Réf.	EAN 4003773-	↔ mm	Ouverture de clé S mm	Ouverture de clé S pouces	Diam. max (d) mm	Carré de connexion pouces	⚖ g	
98 37 10	020578	⚡ 1000V ○ 100%	10,0		18,7	3/8	32	
98 37 11	020585		11,0		20,0	3/8	32	
98 37 12	020608		12,0		21,2	3/8	33	
98 37 13	020615		13,0		22,5	3/8	33	
98 37 14	020622		14,0		23,7	3/8	39	
98 37 17	020639		17,0		27,5	3/8	61	
98 37 19	020646		19,0		30,0	3/8	73	
98 37 5/16"	020684				5/16	16,2	3/8	30
98 37 3/8"	020677				3/8	18,7	3/8	31
98 37 7/16"	020707				7/16	20,0	3/8	31
98 37 1/2"	020554				1/2	22,5	3/8	33
98 37 9/16"	020721				9/16	23,7	3/8	39
98 37 5/8"	020691				5/8	26,2	3/8	51
98 37 3/4"	020660				3/4	30,0	3/8	71
98 37 1/4"	020561				1/4	14,7	3/8	30
98 47 10	020882		⚡ 1000V ○ 100%	10,0		19,5	1/2	63
98 47 11	020899			11,0		20,7	1/2	61
98 47 12	020912			12,0		23,0	1/2	64
98 47 13	020929			13,0		23,2	1/2	64
98 47 14	020943	14,0			24,5	1/2	67	
98 47 16	027287	16,0			26,9	1/2	69	
98 47 17	020967	17,0			28,2	1/2	75	
98 47 18	027294	18,0			29,0	1/2	81	
98 47 19	020974	19,0			30,7	1/2	99	
98 47 22	020981	22,0			34,5	1/2	125	
98 47 24	020998	24,0			37,0	1/2	151	
98 47 27	021001	27,0			41,0	1/2	183	
98 47 1/2"	020875				1/2	23,2	1/2	67
98 47 9/16"	021094				9/16	24,5	1/2	64
98 47 5/8"	021063				5/8	26,9	1/2	72
98 47 11/16"	020905				11/16	28,2	1/2	88
98 47 3/4"	021018				3/4	30,7	1/2	97
98 47 7/8"	021087				7/8	34,5	1/2	124
98 47 1"	020868				1	41,0	1/2	167