



ALFRA HYDRAULIC PUNCHER – AP-65

- Specially developed for assembly applications. Compact and powerful design. Easily portable – flexible in application.
- For punching steel and copper
- Area of application: For punching busbars, general punching tasks in structural and bridge construction, scaffolding etc.

Technical data:

Piston stroke: 18 mm
Punching force: 270 kN

Outreach:

Working pressure max.: 700 bar
Punching range: Punch Ø 5.5 - 10 mm, material thickness max. 8 mm, (S235)
Punch Ø 10 - 21 mm, material thickness max. 10 mm, (S235)

Weight: 16 kg
Dimensions: 220 x 110 x 335 mm

Prod.-No.

Hydraulic puncher AP-65

03260

Tools for copper, aluminium and steel

Ø mm	max. material thickness mm	Prod.-No. Punch	Prod.-No. Die
5.5	5	03265	03275
6.6	6	03266	03276
8.0	6	03285	03290
9.0	8	03267	03277
11.0	10	03268	03278
14.0	10	03269	03279
18.0	10	03270	03280
21.0	10	03271	03281

Other Ø on request



Prod.-No. 03853

As a drive, we recommend our electric-hydraulic pump
AHP 03-1 Prod.-No. 03853



Prod.-No. 03260




Punches and dies for AP-65



PUMP OVERVIEW



Recommended combination Possible combination	 FOOT PUMP	 AHP 03-01	 SC-05 III B	 DSP-120	 LHP 700	 ALH 600
Prod.-No.	02121	03853	03852	02027	02140	03190
 Prod.-No. 02012 / 02013	■ ■	■ ■	■ *	■	■	■
 Prod.-No. 03200SET		■	■ ■			
 Prod.-No. 03250	■	■ ■	■ *	■	■	■
 Prod.-No. 03256	■	■ ■	■ *	■	■	■
 Prod.-No. 03258	■	■ ■	■ *	■	■	■
 Prod.-No. 03260	■	■ ■	■ *	■	■	■
 Prod.-No. 03300	■	■ ■	■ *	■	■	■
 Prod.-No. 03360/03380	■ ■	■ ■				■ ■
 AP 250		■			■	■ ■
 AP 400		■			■	■ ■
* in combination with optional foot switch						

A