

Portrait

ROHRflex
Conduits

FLEXAquick
Connectors

Metal
Conduits





Metal
Conduits
liquid tight

Plastic
Conduits

Special
Conduits



Raccords appropriés
Suitable connectors

		Page
	US-M	7. 10
	US-P	7. 10
	NIMS-M/P	7. 11
	SGL	7. 11

Domaines d'application

- Industrie sidérurgique
- Fonderie
- Chemische Industrie
- Erdöl Raffinerien
- Schiffbau
- Verkehrstechnik
- Bergbau
- Glasfabriken

Application

- Steel industry
- Foundries
- Chemical companies
- Oil companies
- Shipbuilders
- Public transportation
- Mining industry
- Glass factories

Tuyau ignifuge
Tressage de silicate de calcium
avec gainage en silicone

Matériau
Tuyau silicate de calcium
Mantel silicone

- Caractéristiques**
- Revêtement pour câbles et conduites, tuyaux hydrauliques et tuyaux d'eau de refroidissement
 - Pour la protection contre l'incendie, contre les températures élevées et le feu nu, la projection de flammèches et de métal
 - Pour la protection contre les accidents - empêche les brûlures au niveau des garnitures, des échappements ou des tuyaux métalliques chauds




- Propriétés**
- résistant aux intempéries
 - étanche à l'eau
 - largement résistant à l'eau de mer, aux acides et aux huiles
 - résistant à l'abrasion
 - très flexible
 - non inflammable et absence de post-combustion
 - autoextinguible
 - **DIN 5510 [ST2/SR2/S4]**

Fire protection conduit
Calcium-silicate-braiding with
Silicone sheathing

Material
Conduit calcium-silicate-braiding
Sheathing silicone [SI]

- Application**
- Cover for cables and main leads hydraulic hoses and cooling-circuit-hoses
 - For fire protection - protection against high temperatures, open flames and metal-splash
 - For accident protection - no burning on fittings, exhausts or hot metalhoses

- Properties**
- weatherproof
 - watertight
 - widely resistant to seawater, acids and oils
 - abrasive resistant
 - very flexible
 - non-flammable even no afterglow
 - self-extinguishing
 - **DIN 5510 [ST2/SR2/S4]**

N° FLEXA	LN			
rouge red	∅	mm	kg/m	m
2061.809.010	10	10,0 x 17,0	0,119	15
2061.809.015	15	15,0 x 22,0	0,209	15
2061.809.020	20	20,0 x 27,0	0,213	15
2061.809.022	22	22,0 x 29,0	0,239	15
2061.809.025	25	25,0 x 32,0	0,291	15
2061.809.030	30	30,0 x 37,0	0,342	15
2061.809.035	35	35,0 x 42,0	0,390	15
2061.809.040	40	40,0 x 47,0	0,380	15
2061.809.050	50	50,0 x 57,0	0,733	15
2061.809.060	60	60,0 x 67,0	0,750	15

** en couronne
** in rings