



LED drivers _ A7-8-11

C.C.E.A. s.r.l.
Via Vicenza, 80 Altavilla (VI) - Italy
Phone ++39 0444 572083 Fax ++39 0444 572337
www.ccealights.com - ccea@ccealights.com



Direct current electronic drivers for power LED



cod. **A7LED1W**



TECHNICAL FEATURES

Input voltage	230 V ac
Frequency	50/60 Hz
Output voltage	3,2 V dc
Output current	250 mA cost
Power	3 W
IEC class	II
Size (LxbxH)	90x55x50 mm
Degree of protection	IP40



cod. **A8LED5W**



TECHNICAL FEATURES

Input voltage	230 V ac
Frequency	50/60 Hz
Output voltage	7,6 V dc
Output current	260 mA cost
Power	5 W
IEC class	II
Size (LxbxH)	90x55x50 mm
Degree of protection	IP40

cod. **A11LED3W**



TECHNICAL FEATURES

Input voltage	230 V ac
Frequency	50/60 Hz
Output voltage	3,7 V dc
Output current	450 mA cost
Power	3 W
IEC class	II
Size (LxbxH)	90x55x50 mm
Degree of protection	IP40

All the information gathered by this manual can be modified at any time without prior notice and do not imply any obligation by CCEA.