

Datasheet

cod. **K4 - K9**
LED lighting kit

C.C.E.A. s.r.l
Via Vicenza, 80
36077 Altavilla Vicentina (VI) - Italy
Tel. ++39 0444 572083
Fax. ++39 0444 572337
E-mail: ccea@ccealights.com
www.ccealights.com



LED lighting kit made up of stabilized power PSU, magnetic LED and fastening clip.



cod. LED: M011010J     **IP40**

cod. PSU: A4LED1W    **IP40** dimmable

cod. PSU: A7LED1W    **IP40**

K4LED1W: M011010J + A4LED1W dimmable
K9LED1W: M011010J + A7LED1W

ELECTRICAL FEATURES

Voltage	3,8 Vdc
Current	250~350 mA dc
Power	1W
IEC class	II

MECHANICAL AND OPTICAL FEATURES

LED type	Cree XR-E
N. LED	1
LED lifetime	50000 h
Brightness	Narrow beam - Max 25Lumen
Light colour	5000 °K
Spotlight LED	25x25x14mm
Fastening	Magnetic
Switch	Embodied in PSU
Degree of protection	IP40
Colour	Black

PSU FEATURES

Code	Vin	Vout	Iout	W	Size
A4LED1W dimmable	230 Vac	3,8 Vdc	250mA	1 W	90x55x50mm
A7LED1W	230 Vac	3,8 Vdc	250mA	3,5 W	90x55x50mm

ORDER CODES

M011010J	spotlight LED
A4LED1W	PSU dimmable for M011010J (K4)
A7LED1W	PSU for M011010J (K7)

Flow light from working surface

H 220mm

∅ (mm)	lux
120	290 lux
200	230 lux
250	180 lux

H 500mm

∅ (mm)	lux
200	160 lux
300	150 lux
400	140 lux

All the information gathered by this manual can be modified at any time without prior notice and do not imply any obligation by CCEA.