

Datasheet

cod. **K40 LED 1W**
LED lighting kit

C.C.E.A. s.r.l
Via Vicenza, 80
36077 Altavilla Vicentina (VI) - Italy
Tel. ++39 0444 572083
Fax. ++39 0444 572337
E-mail: ccea@ccealights.com
www.ccealights.com



LED lighting Kit made up of stabilized power PSU, anodized aluminum LED illuminator with 40° lens, chromium plated stainless steel gooseneck arm, aluminum anodized magnetic plate for fastening.

cod. LED: L40LED1W **IP40**

cod. PSU: A7LED1W **IP40**

ELECTRICAL FEATURES

Voltage	3,8 Vdc
Operating Current	250~350 mA dc
Power	1W
IEC class	II

MECHANICAL AND OPTICAL FEATURES

LED type	Cree XR-E
N. LED	1
LED lifetime	50000 h
Brightness	Narrow beam - 40° lens
Light colour	5300 °K
Spotlight LED	Ø25xL32,5mm
Arm	Ø6xL200mm
Magnetic plate	Ø30xH23mm
Fastening	Neodymium magnetic base
Switch	Embodied in PSU
Degree of protection	IP40
Colour	Aluminum

PSU FEATURES

Code	Vin	Vout	Iout	W	Size
A7LED1W	230 Vac	3,8 Vdc	250mA	3,5 W	90x55x50mm

ORDER CODES

L40LED1W	LED lamp
A7LED1W	PSU for L40LED1W

Flow light from working surface - H.1000mm

Ø (mm)	lux
100	820 lux
200	600 lux
300	450 lux
400	350 lux

Fastening



Magnetic base

All the information gathered by this manual can be modified at any time without prior notice and do not imply any obligation by CCEA.