

Datasheet

cod. **K5 - K10**

LED lighting kit

C.C.E.A. s.r.l.
Via Vicenza, 80
36077 Altavilla Vicentina (VI) - Italy
Tel. ++39 0444 572083
Fax. ++39 0444 572337
E-mail: ccea@ccealights.com
www.ccealights.com



LED lighting kit made up of stabilized power PSU, n.2 magnetic LED and fastening clip.

cod. LED: M021020J     **IP40**

cod. PSU: A5LED5W    **IP40** dimmable

cod. PSU: A8LED5W    **IP40**

K5LED1W: M021020J + A5LED5W (dimmable)

K10LED1W: M021020J + A8LED5W

ELECTRICAL FEATURES

Voltage	7,6 Vdc
Current	250~350 mA dc
Power	2x1W
IEC class	II

MECHANICAL AND OPTICAL FEATURES

LED type	Cree XR-E
N. LED	2
LED lifetime	50000 h
Brightness	Narrow beam - Max 25Lumen
Light colour	5000 °K
Spotlight LED	25x25x14mm
Fastening	Magnetic
Switch	Embodied in PSU
Degree of protection	IP40
Colour	Black

PSU FEATURES

Code	Vin	Vout	Iout	W	Size
A5LED5W dimmable	230 Vac	7,6 Vdc	350mA	3 W	90x55x50mm
A8LED5W	230 Vac	7,6 Vdc	260mA	5 W	90x55x50mm

ORDER CODES

M021020J	spotlight LED
A5LED5W	PSU dimmable for M021020J (K5)
A8LED5W	PSU for M021020J (K10)

Flow light from working surface

H 220mm

Ø (mm)	lux
150	560 lux
200	250 lux
240	180 lux

H 500mm

Ø (mm)	lux
245	260 lux
350	170 lux
450	140 lux

All the information gathered by this manual can be modified at any time without prior notice and do not imply any obligation by CCEA.